

## Industrial weighing with big display

Fast, economic, easy to use



## IND220/ IND225

## Good functionality makes the difference

- Large 7-segment LED display
- Table, column or wall mount
- Connectivity via Optically Isolated RS232
- Enhances life of the scale

The large display for the indicator family IND22x is unique in its class. It offers applications like checkweighing / classifying, counting, x10, or unit switch. All this is packed in a stylish and functional designed plastic housing or also available with a stainless steel enclosure.





	IND220	IND225
Housing	Plastic	Stainless steel (SS304)
Dimensions WxHxD	220x130x137mm / 8,7x5,1x5,4"	220x180x132mm / 8,7x7,1x5,2"
Display	6 characters, 7-segment LED, height: 30mm / 1,2"	
Internal resolution	20,00,000	20,00,000
Power supply	100240VAC	100240VAC
Load cell connection	max. 4 x $350\Omega$ load cells	max. 4 x 350 $\Omega$ load cells
Power supply load cell	5VDC	5VDC
Applications	Counting, checkweighing / classifying, x10, or unit switch (lb, kg)	
A/D update	27 times / sec	27 times / sec
Protection	IP54	IP67
Interface	RS232	RS232
Approvals	NTEP 10000d	NTEP 10000d
Linearity	3-point	3-point

www.mt.com

Visit for more Information




















Tel: 91 - 22 - 2803 1111
Email: sales.mtin@mt.com
Website: www.mt.com



